

EPOCA S / S TANK

RANCILIO

coffeeing the World



EPOCA S / S TANK


Sparking versatility

The semi-automatic control of this version makes it extremely simple to use and reliable in all situations. EPOCA S is also available in the TANK version, with an independent water tank that allows it to be used without connection to a main water supply.

1 C-LEVER (Rancilio Patent) The new standard steam valve with a special control knob and ergonomic design is complete with open-stay and open-close functions. The valve has a very short travel distance, and is operated by rotating it just 25°. Turning it upwards, it opens and remains in this position. Turned downwards, it automatically closes when released. Rapidity, precision and ergonomics: maximum user comfort for daily tasks.

2 TANK [only for 1G] The special feature of the Epoca 1G Tank version is the presence of an independent water tank that allows it to be used without connection to a main water supply. This characteristic makes it an extremely versatile model.

3 GRID SYSTEM To make cleaning and maintenance easier, Rancilio has equipped all its products with a revolutionary work surface. Support grids come in a scratchproof polymer, with an efficient liquid collection system that keeps the work surface clean and protects cups against unsightly marks left by drops of coffee. The grids can be removed for washing in a dishwasher. Rancilio quality also means attention to details.



Technical Features

| |
|--|
| independent heat exchangers |
| electric heating |
| incorporated volumetric pump |
| boiler pressure gauge |
| automatic water level control |
| housing in stainless steel, base e fianchi in Hdpe e Abs |

Endowments, accessories

ENDOWMENTS: 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands for version with 2 groups, 1 steam wand for version with 1 group, 1 hot water dispenser, coffee tamper, blind filter and measuring scoop.

ACCESSORIES: DP automatic or manual water softener, MD dosing grinder.

Colors

metallic red and metallic grey

Technical Data

1 GROUP

| | | | |
|--|---------------------------------|-------------------------|--------------------|
| dimensions (wxdxh) 15.1 x 22.1 x 18.9 inches | weight 77 Lb | boiler (lt) 4 | Hz 50/60 |
| boiler power 1600 W (120 V) - 1700 W | voltage 120 / 220-240 | | |

1 GROUP TANK

| | | | |
|--|---------------------------------|--------------------------------|--------------------|
| dimensions (wxdxh) 15.1 x 22.1 x 18.9 inches | weight 62 Lb | boiler (lt) 4 | Hz 50/60 |
| boiler power 1600 W (120 V) - 1700 W | voltage 120 / 220-240 | water tank 0.5 usgal | |

2 GROUPS

| | | | |
|--|--|--------------------------|--------------------|
| dimensions (wxdxh) 30.7 x 22.1 x 18.9 inches | weight 117 Lb | boiler (lt) 11 | Hz 50/60 |
| boiler power 3200 W (120 V) - 4300 W | voltage 120 / 220-240 / 380-415 3N | | |



Standard



On demand

